



The Lumens[®] OIP-D50C is a powerful system solution for controlling the AVoIP extender over a network. It allows users to easily control and configure directly through the Web GUI. It provides flexible, high-efficient and cost-effective Pro A/V system solutions. It is applicable for a wide range of environments, such as sports bars, school campuses, and house of worship, etc.

Key Features


- Centralized management of distributed encoders and decoders *with OIP series
- Intuitive Web-based GUI for AV distribution and control
- · Effortless sources switching and video wall deployment
- Supports PoE for easy installation

Key Feature Details

Video Wall Deployment



Group Control



Supports Touch Screen



Macro Instruction



Drag & Drop



Schedule





Specifications

INTERFACE	
Output	1 HDMI 1.4
Control	 IR Extender (3.5mm) RS-232 (3-pin Terminal Block) Trigger (10-pin Terminal Block) USB 2.0 (Type-A) Ethernet (RJ-45)
Reserved Port	1 RS-232 (5-pin Terminal Block)
VIDEO	
Output Signal Type	HDMI 1.4 1080p60
AUDIO	
НОМІ	LPCM (8 Channels) / Bitstream / HD Bitstream
POWER	
Power Supply	5V/2.6A DC (Locking) PoE (802.3af)
Power Consumption	2.99W
ENVIRONMENTAL	
Operating Temperature	0°C ~ 40°C
Operating Humidity	20~80%, non-condensing
Storage Temperature	-40°C ~ 60°C
Storage Humidity	90%, non-condensing
ENCLOSURE	
Housing	Metal
Weight	0.55lbs (0.25kg)
Dimensions (W×H×D)	Case Only: 9.11" x 0.98" x 4.25" (231.5mm x 25mm x 108mm) All Inclusive: 9.11" x 0.98" x 4.61" (231.5mm x 25mm x 117mm)



Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone : +1-866-600-0988 Fax : +1-510-252-1389

Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone : +32-473-58-38-95 Fax : +32-2-452-76-00

