# VC-B10U Ultra-HD ePTZ USB

# The Lumens<sup>™</sup> VC-B10U is a high-definition ePTZ camera specifically designed for small meetings, classrooms and distance learning. It supports USB 3.0 and is plug-and-play with just one USB cable. Thanks to its built-in TV mount it's easily installed on the TV or on the screen, and equipped with a 120° wide viewing angle and can even enlarge to 3x magnification, attendees appear clear. In addition, it has a built-in microphone, best suited for distance learning or videoconferencing.

#### **Key Features**

- Supports USB 3.0 / 2.0 plug & play
- 4K image sensor with 12 Megapixel
- Output resolution up to 3264 x 2448
- Panoramic 120° viewing angle
- Maximum 3x sensor zoom, and 8x digital zoom
- ePTZ, Remote control
- Supports 64 preset positions
- Built-in microphone with beam forming and noise suppression technology

Compatible with all popular applications and cloud systems:



Lumens

S Lync Webex Zoom 😽 GoTo Meeting BlueJeans

#### **More Details**



#### USB 3.0 Plug & Play

The VC-B10U uses standard UVC drivers. There is no need to install special USB drivers. USB 3.0 is 10 times faster than the USB 2.0 standard and it features low latency and non-compress output.



#### Excellent Image Quality

Google Meet

The VC-B10U has a professional 12 megapixel image sensor that features low noise, high resolution, and vivid color reproduction and presents an excellent image quality even under insufficient light conditions.

Microsoft Teams



## Panoramic Viewing Angle

The VC-B10U has a panoramic 120° viewing angle that helps users achieve a wider viewing area.



#### Ea au co ca So

## Easy control

Easy control like Pan, Tilt, Zoom and settings by IR remote controller and Lumens USB PTZ camera controller software. Supports Windows, MAC OS and Android.



#### 3x Sensor Zoom

The 3x sensor zoom can magnify viewing for more details, shapes, color and it's still clear without any distortion.

#### **64 Preset Positions**

The VC-B10U has 64 preset settings for pan, tilt, zoom, focus, and white balance modes for more effective and efficient video recording.



#### Adaptive Microphone Design

The VC-B10U with two built-in microphones is a best fit for distance learning or videoconferencing. Speech enhancement can be utilized with Microphone Beamforming and noise suppression technology.



# Easy Integration on the Screen

The USB 3.0 cable has a 90 degree design allowing the VC-B10U to install effortlessly for any display size.

## **Product Specifications**

| Sensor                   | 1/2.3" 12.35 MP CMOS  | ePTZ                           | Support                                      |
|--------------------------|---|--------------------------------|--|
| Video Output             | 3264x2448 10 fps<br>3264x1836 10 fps<br>1920x1080 60 / 30 fps<br>1280x720 60 / 30 fps<br>960x540 30 fps<br>640x480 30 fps<br>640x360 30 fps | Preset Positions               | IR: 6 Sets<br>USB: 64 sets                   |
|                          |   | Video Format                   | YUV / MJPEG                                  |
|                          |   | Video Output (HD)<br>Interface | USB 3.0 (USB 2.0 Compatible)                 |
|                          |   | Microphone                     | Build in 2 microphones                       |
| Aperture                 | F1.8  | White Balance                  | Manual / Auto                                |
| View Angle               | 120° (Diagonal), 110° (Horizontal)  | Exposure Control               | Auto   |
| Minimum Object Distance  | 50 cm   | Brightness Control             | Yes  |
| Remote Control           | Yes   | Back Light Comp                | On / Off                                     |
| Zoom (Lossless)          | 2x for 1080p (1920x1080)<br>3x for 720p (1280x720)  | Focus System                   | Fixed Focus                                  |
| Digital Zoom             | 8x  | 2D Noise Reduction             | Yes  |
| Camera Control Interface | IR remote control / USB   | TV Mount                       | Built-in                                     |
| Driver                   | UVC / UAC   | Weight                         | Main Unit : 120g<br>Main Unit & Shelf : 180g |

## **I/O CONNECTIONS**





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone: +1-866-600-0988 Fax: +1-510-252-1389

Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone : +32-473-58-38-95 Fax : +32-2-452-76-00



Lumens is the registered trademark of Lumens Digital Optics Inc. Changes in specification or design may be done without notification. \*The warranty policy may be different depending on the sales region, please contact your local salesperson.