







VS-KB21N

IP Camera Controller with NDI



VS-KB21N is a fully-featured IP controller suitable for use with box and PTZ cameras. Its built-in display allows the user to preview the IP or NDI stream of each connected camera. This makes it easier and quicker to frame each shot and to set up presets.

- Controls up-to total of 255 IP-connected or NDI-connected cameras
- Quick access control of exposure, white balance, focus, PTZ speed and 2 user-assignable keys

Key Features

- Supports RTSP and NDI HX Stream Preview on LCD screen
- Supports RS-232, RS-422, and Ethernet control
- Supports VISCA, VISCA Over IP and NDI control protocols



NDI Workflows

VS-KB21N identifies NDI cameras on the IP network and allows monitoring and full device control. The controller also supports the VISCA protocol making it a supremely versatile unit.



3" LCD Preview Screen

The low latency preview screen monitors up-to 255 IP streams simultaneously. For precise framing, the operator can switch to a single stream layout enabling full screen video preview.



Quick Camera Select

With 7 hot keys, the operator can instantly select the PTZ or box camera they want to control. This makes it easier than ever to manage a multi-camera production.



Quick Settings

The LCD screen displays all key camera parameters including iris, shutter and gain. This allows quick and accurate set-up of each camera.



Product Specifications

| Comm. Interface | RS-232 / RS-422 / IP |
|-----------------------|---|
| Display | 3" LCD |
| Joystick | 4-axis (Pan / Tilt / Zoom) |
| Speed Control | x1 (1 Knob) |
| Zoom Control | x1 (Zoom Seesaw Lever) |
| Gain Control | R/B Gain |
| Focus Control | Auto / Manual |
| Assign Button | x2 |
| Keypad with backlight | Yes |
| Stream Preview | RTSP / NDI HX2 / NDI HX3 |
| Control Protocol | NDI / VISCA / VISCA Over IP |
| Baud Rate | 2400 / 4800 / 9600 / 38400 / 115200 bps |
| Camera Address | 1~255 |
| Preset | 255 |
| Power | DC12V / PoE |
| Power Consumption | PoE : 5W DC In : 5W |
| Dimension(WxHxD) | 11.89" x 5.63" x 4.41" (302 mm x 143mm x 112mm) |
| Weight | 2.8 lbs (1.3 kg) |

I/O Connections





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone: +1-866-600-0988 Fax: +1-510-252-1389 Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone : +32-473-58-38-95 Fax : +32-2-452-76-00



Lumens is the registered trademark of Lumens Digital Optics Inc. Changes in specification or design may be done without notification. *The warranty policy may be different depending on the sales region. Please contact your local salesperson for details.